

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)


PCT

(10) International Publication Number
WO 2004/044357 A1

- (51) International Patent Classification⁷: E05B 15/02, 47/00
- (21) International Application Number: PCT/AU2003/001518
- (22) International Filing Date: 13 November 2003 (13.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2002952629 13 November 2002 (13.11.2002) AU
- (72) Inventors; and
(75) Inventors/Applicants (for US only): BURKE, Christopher, John [AU/AU]; 48 Margate Street, Ramsgate, NSW 2217 (AU). HARWARD, Richard, Bruce [AU/AU]; 8 Mordialloc Place, Robina, QLD 4226 (AU).
- (74) Agent: SPRUSON & FERGUSON; G.P.O. Box 3898, Sydney, NSW 2001 (AU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
- (71) Applicant (for all designated States except US): SE-CURICOM (NSW) PTY LTD [AU/AU]; 48 Margate Street, Ramsgate, NSW 2217 (AU).

[Continued on next page]

(54) Title: SOLENOID OPERATED LATCHING STRIKE



(57) Abstract: A latching strike assembly for a door lock has a body (1, 201, 301) adapted to be fitted to a door jamb. A latching strike (4, 204, 304) is mounted to the body (1, 201, 301) and defines a boundary of the latch bolt recess (3, 203, 303) of the body (1, 201, 301). The latching strike (1, 204, 304) is pivotable between open and closed positions for releasing and retaining a latch bolt (100) respectively. A bi-stable detent (7, 207, 307) is displaceable between a stable locking position at which the detent (7, 207, 307) engages the latching strike (4, 204, 304) to lock the latching strike (4, 204, 304) in the closed position and a stable unlocking position at which the detent (7, 207, 307) is disengaged from the latching strike (4, 204, 304), thereby enabling the latching strike (4, 204, 304) to be deflected to the open position by the latch bolt (100). The detent (7, 207, 307) may be displaced between the locking and unlocking positions either by a single solenoid (314) or by two separate solenoids (14, 15, 214, 215).

WO 2004/044357 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*